

Case Former Options	Option Definition	When Option Should Be Used
Tape Cartridge Options		
CaseLocker CAC50 2"	Heavy Duty 2" wide tape cartridge that tapes up to 80 ft./min	When 2" tape is being applied to a case without void. Spring adjustment allows taping of various strength cases.
CaseLocker CAC51 3"	Heavy Duty 3" wide tape cartridge that tapes up to 80 ft./min	When 3" tape is being applied to a case without void. Spring adjustment allows taping of various strength cases.
CaseLocker CAC60 2"	2" wide tape cartridge that tapes up to 100 ft./min	When 2" tape is being applied to a weak corrugated case. Light touch roller arm design requires minimal force which facilitates weak corrugated cases
CaseLocker CAC60H 2"	2" wide tape cartridge that tapes up to 155 ft./min with the capability to do 200 ft./min	When the high speed option is needed and 2" tape is applied to case
CaseLocker CAC61 3"	3" wide tape cartridge that tapes up to 100 ft./min	When 3" tape is being applied to a weak corrugated case. Light touch roller arm design requires minimal force which facilitates weak corrugated cases
CaseLocker CAC61H 3"	3" wide tape cartridge that tapes up to 155 ft./min with the capability to do 200 ft./min	When the high speed option is needed and 3" tape is applied to a case
Motor Options		
NEMA 4 Electrics	1/3 HP (CF-25) or 1/2 HP (CF-50) 50 or 60 Hz	Protects electrical components in a damp, humid, or wash-down environment
NEMA 12 Electrics	1/3 HP (CF-25) or 1/2 HP (CF-50) 50 or 60 Hz	Protects electrical components in a dusty environment
Cold Room Package	Depending on the temperature, the cold room package may include a heater enclosure and an air dryer assembly or just an air dryer assembly. The package ensures that electronics and pneumatics function properly under colder ambient temperatures that may cause condensation	If Case Former is located in a cold environment with an ambient temp between 40° F and 33°F it will only require an air dryer assembly. Ambient temps of 32°F and below will include both the air dryer assembly and heater enclosure
Air Dryer For Pneumatic System	Removes moisture from the air going into the machine. Includes water separator and fittings	A cold environment when there may be condensation build up, or a humid environment
Auto Central Lube System	feeds grease to all grease ports in machine. The lubrication frequency is adjustable and manually preset by the operator or maintenance team.	Saves time, more efficient, and ensures that all ports are greased
Operator Awareness Options		
Low Hopper Alarm	Stack light indicating that boxes are running low	If there is not an operator present at the Case Former
Low Tape Alarm	Stack light indicating that tape is running low (bottom only)	If there is not an operator present at the Case Former
Box Jam Detector	Stack light indicating that a box jam occurred	If there is not an operator present at the Case Former
Additional Options		
Conveyor Height	Increases machine discharge height up to 32" to match existing conveyor height	When existing conveyors are higher than standard exit on machine
Mirror Image (CF-25 Only)	change case flow to left to right and operator controls. Hold down sled, tape head, main drives, box opening & hopper setting remain standard	Depending on case former set up and location, cases may need to flow in opposite direction
Mirror Image (CF-50 Only)	Changes flow of boxes to left to right and operator controls from operator side	Depending on case former set up and location, cases may need to flow in opposite direction
Spare Parts Kit	A kit with a set list of recommended parts for repairing high wear items	Best to buy at point of sale. Saves time on replacing high wear items
Caster System	Adds an additional 5 3/4" (5/8" on CF-25) To machine height and includes 4 casters (CF50 gets 8 casters)	Allows for easy transfer of case former from one location to another
Extended Capacity Hopper	Doubles capacity of hopper from approximately 165 single wall RSC style containers to approximately 330	Cuts down the amount of time the case former is down to reload the hopper and runs more efficiently
High Speed Option CF-25 Only	Increases through-put speed from 10 cases per min up to 15 cases per min. Note: This Option Will Reduce The Case Size Range to 15" L x 12" W max	When more through-put is needed to keep up with demand
High Speed Option CF-50 Only	Increases through-put speed from 14 cases per min up to 20 cases per min. Note: This Option Will Reduce The Case Size Range to 18" L x 12" W max	When more through-put is needed to keep up with demand